

Remarks

Claims 1-6 and 8-19 are pending in this application. The Office Action states that claims 9-13 and 19 are allowed and claim 8 contains allowable subject matter. By this Amendment, claims 1, 3-6, 9 and 14-19 are amended.

Applicant appreciates the courtesies shown to Applicant's representative by Examiners Nobahar and Barron in the March 24 personal interview. Applicant's separate record of the substance of the interview is incorporated into the following remarks. Specifically, claims 1, 3, 4-6 and 14-18 are amended to comply with the Examiners' helpful suggestions made during the interview.

Reconsideration based on the above amendments and following remarks is respectfully requested.

I. Specification

The Office Action states that a substitute specification in proper idiomatic English and in compliance with 37 C.F.R. §1.52(a) and (b) is required. Applicant has provided the required substitute specification and respectfully submits that the Specification is in compliance with 37 C.F.R. §1.52(a) and (b). No new matter is added in the Substitute Specification.

Applicant respectfully submits that the terms identified by the Examiners during the interview are clearly described in the specification. In particular, Applicant respectfully submits that the following definitions of the following terms identified in the February 3 Office Action are clear from the specification as a whole:

1) encryption target data is data or information that has been encrypted and is part of the lock data;

2) signature target data also is data or information that has been encrypted and part of the lock data on which a signature to be verified by use of the public key is to be written;

- 3) encryption target data is data that is intended to be encrypted;
- 4) target range is a range of data that is intended to be encrypted;
- 5) target data is the encrypted target range;
- 6) judgment target is the individual lock that is being judged; and
- 7) signature target is the signature being validated.

II. Claim Rejection Under 35 USC §112

The Office Action rejects Claims 3, 16 and 17 under 35 U.S.C. §112, second paragraph, as being indefinite. This rejection is overcome by the amendments to these claims.

Withdrawal of the rejection of claims 3, 16 and 17 is respectfully requested.

IV. Claim Rejection Under 35 USC §102

Claims 1-6, 14-16 and 18 are rejected under 35 U.S.C. §102(e) as being unpatentable over U.S. Patent No. 6,118,874 to Okamoto et al. (Okamoto). This rejection is respectfully traversed.

As discussed at the March 24 personal interview, it is respectfully submitted that Okamoto fails to disclose or suggest all of the features recited in claims 1-6, 14-16 and 18. Specifically, Okamoto fails to disclose or suggest the feature of an encrypted private key as recited in claims 1-6 and 14-16 and 18. The encrypted private key is formed by encrypting the group private key with the common key.

As discussed in the personal interview and stated in the Interview Summary, Examiners Nobahar and Barron agreed that Okamoto does not disclose or suggest an encrypted private key as recited in claims 1, 3-6 and 14-18. Okamoto merely discloses a public key that is used to encrypt a common key.

Claims 1, 3-6 and 14-18 are amended to more clearly recite this feature and to distinguish the group public keys and group private keys from the group member public keys and group member private keys.

Regarding claim 6, it respectfully submitted that Okamoto fails to disclose or suggest all of the features recited in claim 6. Specifically, Okamoto fails to disclose or suggest the feature of encrypting a modified group private key by use of a common key to generate an encrypted modified private key as recited in claim 6.

It is respectfully submitted that since claim 2 depends from claim 1, claim 2 is allowable at least for the same reasons as claim 1.

It is respectfully submitted that since claim 8 depends from claim 5, claim 8 is allowable at least for the same reasons as claim 5.


Withdrawal of the rejection of claims 1-6, 14-16 and 18 is respectfully requested.

VI. Conclusion

In view of the foregoing, Applicant respectfully submits that this application is in condition for allowance. Favorable reconsideration and prompt allowance of claims 1-6 and 8-19 are earnestly solicited.

Should the Examiner believe that anything further would be desirable in order to place this application in even better condition for allowance, the Examiner is invited to contact Applicant's undersigned representative at the telephone number listed below.

Respectfully submitted,



James A. Oliff
Registration No. 27,075

David E. Brown
Registration No. 51,091

JAO:DEB/tbh

Attachments:

Petition for Extension of Time
Substitute Specification (Clean Version)
Substitute Specification (Marked-Up Version)

Date: June 3, 2004

OLIFF & BERRIDGE, PLC
P.O. Box 19928
Alexandria, Virginia 22320
Telephone: (703) 836-6400

<p>DEPOSIT ACCOUNT USE AUTHORIZATION Please grant any extension necessary for entry; Charge any fee due to our Deposit Account No. 15-0461</p>
--



METHOD FOR GROUP UNIT ENCRYPTION/DECRYPTION, AND METHOD AND APPARATUS FOR WRITING SIGNATURE

BACKGROUND OF THE INVENTION

1. Field of Invention

[0001] This invention relates to a public key cryptography technology, and more particularly relates to a system for allowing only an arbitrary member in a group to decrypt and write ~~the~~ a signature by use of a group key which is allowed to be used by only the group member.

2. Description of Related Art

[0002] A Cryptography system ~~called~~ referred to as a public key cryptography system is disclosed in U.S. Patent No. 4,200,770. In the public key cryptography system, a public key is used for encrypting a plain text and a private key is used for decrypting a cryptography text back to a ~~the~~ plain text. The public key and the private key are different from each other. The public key may be disclosed to the public and therefore, ~~literally to be~~ known by the public. On the other hand, in ~~the~~ conventional cryptography system systems (referred alternatively to as a private key cryptography system, a symmetric key cryptography system, and or a conventional cryptography system), since the same key ~~has been~~ is used for encryption and decryption, ~~and how to secure the~~ maintaining confidentiality has been ~~the a~~ most serious ~~problem, problem~~. However, ~~however~~ in ~~this a~~ public key cryptography system, maintaining the confidentiality of an encryption key is not necessary ~~needless~~. In the case that the number of persons who ~~communicates~~ communicate encrypted documents is n , $n \times (n - 1) \div 2$ keys are necessary for the conventional cryptography ~~encryption-decryption~~ common key system, but only n keys are necessary for the public key cryptography system, this is the advantage of the public key cryptography system. In addition, the public key cryptography system is advantageous in that the same frame can be used in writing the signature of each person, namely encryption processing by each person by use of the private key. For example, a cryptography communication member P having the private key A converts a communication document X by use of the private key A, and sends the converted document Y and the communication document X to another member Q, then the member Q converts the converted document Y by use of the public key B of the member P and can confirm that it is surely the document that is sent by the member P if the conversion result of Y is identical with X. As

described herein above, the public key cryptography system is ~~advantageous in several points, which has several advantageous over~~ the conventional cryptography system ~~does not have~~.

[0003] Japanese Published Unexamined Patent Application No. Hei 7-297818 discloses the structure of allocation of the public key and the private key to a group. This system is based on the assumption that a group private key is embedded in a physical ~~substance substance~~, such as a ~~card card~~, and a group member is ~~carrying this card~~ consistently always has the card in his or her possession. The problems associated with management of the key ~~is realized based on the physical substance that is~~ such as when the card is separated from the everlasting existence namely an individual, are alleviated by structuring the cryptography system of the above-mentioned private key and public key using ~~the substance namely the card~~.

[0004] In the public key cryptography system, ~~the everlasting existence such as an individual is set~~ established as an independent unit. Therefore, the public key cryptography system cannot function efficiently fully in the case ~~that it is necessary to set~~, for example, that it is necessary to establish a plurality of members, ~~other rather~~ than an individual, as a single unit. Further, the system in which a card as described herein above is ~~used is further disadvantageous~~ disadvantaged in that a hardware namely a ~~because the card must be used inevitably, a card itself must be and managed, managed. and the verification~~ Verification of a card holder is problematic when the ~~card holder misses the card is not available~~ due to loss or theft, ~~in other word, because~~ it is difficult to verify the card holder in due course.

[0005] ~~For example, A cooperative working unit may consist of an organization such as a department, a section, and a company unit, in a company is a cooperative working unit, and also an independent organization which is independent from hierarchical organizations such as a task force consisting of a plurality of individuals individuals. is a cooperative working unit. The confidentiality Confidentiality should be maintained between the inside and the outside of within a cooperative working unit, but on the other hand hand, the information should be common among available to individual members in the inside within the cooperative working unit.~~ A cryptography system which allows an arbitrary member of the cooperative working unit to decrypt or write a signature on the common information is required.

[0006] Further, in some ~~occasion occasions~~ when a member of the cooperative working unit is required to change, for example, to add or to delete the information, ~~therefore~~ the cryptography system should be allowable for a member to ~~operate easily for~~ facilitate such

~~changing a change. Further, to take a part of the~~ Regarding a position such as an officer officer, ~~like for example~~ a chief of personnel department in a company as in a cooperative working unit, it is required that specific and continuous confidentiality corresponding to the role position should be maintained independently of a specific individual who ~~takes a part of the role at some time point is acting in a particular capacity in the form which is acceptable of the change~~ regardless of the individual ~~who takes a part of the role assuming the position.~~

[0007] The present invention provides a cryptography system for solving the above-mentioned problem. It is an object of the present invention to provide a cryptography system in which a public key cryptography system can be used in group units, each of which is a group consisting of components of individuals and groups instead of individual units so that members who belong to a specific group can decrypt the cryptography.

[0008] Further it is another ~~object~~ objective of the present invention to provide a signature system which enables an arbitrary member who belongs a specific ~~group~~ group, to write a signature and to verify that a signature on a signed document is the signature written by a member who belongs to the specific group.

SUMMARY OF THE INVENTION

[0009] According to the present invention, to achieve the above-mentioned ~~object~~, objectives, in a method for encryption executes, a step ~~for~~ of storing a group public key, an encrypted private key formed by encrypting a group private key corresponding to the group public key by use of a common key, and lock data which includes a plurality of encrypted common keys generated by encrypting the common key by use of respective public keys of the group member, and a step ~~for~~ of encrypting encryption target data by use of the public key of the lock ~~data~~ data. ~~are executed.~~

[0010] In this structure, because the lock data includes the ~~encrypting~~ group public key, the cryptogram which is formed by encrypting the corresponding group private key by use of the common key, and the cryptogram formed by encrypting the above-mentioned common key by use of the public keys of the group members, a group member can acquire the common key by use of the private key of the member itself and further decrypt it by use of the common key to acquire the group private key to be used for decrypting the cryptogram. As described herein ~~above~~, by encrypting the information by use of the public key of the lock data, it is possible to transmit the information without leakage of the information outside of the group. ~~to the outside of the group/member.~~

[0011] In this structure, the above-mentioned encryption target data is used for decrypting the encrypted information. For example, ~~so-called a decryption~~ cryptography scheme is realized using this the common key as the decryption key. ~~as a common key.~~ In other words, the common key which has been encrypted by means of the public key cryptography system using the lock ~~data-data~~, is sent to a group member, and the group member decrypts the encrypted common key by use of the lock data. ~~Further~~ Further, the cryptogram encrypted by use of the common key is decrypted by use of the decrypted common key.

[0012] Further, according to the present invention, to achieve the above-mentioned ~~object, objective,~~ in the method for decrypting a cryptogram, executes a step for of storing a public key, an encrypted private key formed by encrypting a private key corresponding to the public key by use of a common key, and lock data which includes a plurality of encrypted common keys generated by encrypting the common key by use of respective public keys of the group members; a step for of decrypting one of the encrypted common keys included in the lock data by use of the private key corresponding to the group/member to generate the common ~~key, key;~~ a step for of decrypting the encrypted private key included in the lock ~~data data,~~ by use of the decrypted common key to generate the private ~~key, key;~~ a step for of acquiring encryption target data encrypted by use of the public key, and a step for of decrypting the encrypted encryption target data by use of the decrypted private ~~key key.~~ are executed.

[0013] In this structure, a ~~group/member~~ group member can acquire the private key of the lock data as in the case described ~~herein~~ above. An arbitrary member can easily decrypt a cryptogram encrypted by use of the public key of the lock data. On the other hand, any one who is not a member cannot decrypt the cryptogram.

[0014] Further, according to the present invention, to achieve the above-mentioned ~~object, objective,~~ in a method for writing a signature, executes a step for of storing a public key, an encrypted private key formed by encrypting a private key corresponding to the public key by use of a common key, and lock data which includes a plurality of encrypted common keys generated by encrypting the common key by use of respective public keys of the ~~group/member~~ group member; a step for of decrypting one of the encrypted common keys included in the lock data by use of the private key corresponding to the group/member to generate the common ~~key, key;~~ a step for of decrypting the encrypted private key included in the lock data by use of the decrypted common key to generate the private ~~key, key;~~ a step for

of storing and acquiring signature target data on which a signature to be verified by use of the public key is to be written, and a step ~~for~~ of writing a signature on the signature target data by use of the decrypted private ~~key~~ key. ~~are executed.~~

[0015] In this structure, because only the ~~group/member~~ group member can acquire the private key corresponding to the public key of the lock data as in the case described ~~herein~~ above, the data is verified by use of the private key to thereby write a signature of a ~~group/member~~ group member. A member who acquires the data with a signature can verify the signature by use of the public key of the lock data.

[0016] Further, according to the present invention, to achieve the above-mentioned object, in the method for generating lock data, ~~executes~~ a step ~~for~~ of acquiring a pair of a public key and a private ~~key~~ key; a step ~~for~~ of acquiring a common ~~key~~ key; a step ~~for~~ of encrypting the private key by use of the common key to generate an encrypted private ~~key~~ key; a step ~~for~~ of encrypting the common key by use of public keys of respective ~~group/members~~ group member to generate corresponding encrypted common ~~key~~ key; a step ~~for~~ of combining the public keys, the encrypted private ~~key~~ key; and the encrypted common keys to generate lock ~~data~~ data. ~~are executed.~~

[0017] In this structure, because the lock data includes the cryptogram of the private key of the lock data encrypted by use of the public keys of the ~~group/members~~ group member, only the ~~group/member~~ group member can decrypt a cryptogram and write a signature.

[0018] In this structure, the above-mentioned private key is modified by use of a function (including an inverse function) which is not a one-directional function (~~including an inverse function~~), and the modified private key is encrypted by use of the common key for holding.

[0019] Further, a function for generating seed may be used when the common key is encrypted by use of the public key of the ~~group/member~~ group member. In detail, the public key of the ~~group/member~~ group member is calculated by use of a desired function such as hash function, and the combination of the value of this hash function and the above-mentioned common key (desired calculation, bit catenation) is encrypted by use of the public key of the ~~group/member~~ group member. Because a ~~seed~~-different seed for each public key of each ~~group/member~~ group member is added and the encryption target is varied, no hint is given, even though a plurality of cryptograms are available.

[0020] Further in this structure, a ~~group/member~~ group member may be any one of an individual, a group of individuals, an organization, and a position in an organization.

[0021] The above-mentioned lock data may be managed in unit of the above-mentioned lock data. A user can use a plurality of lock data as if the plurality of the lock data ~~ware-were~~ a bundle of locks. The above-mentioned lock data may be stored in a server to which clients can access.

[0022] The above-mentioned lock data may be structured so as to include a public key for verifying a ~~signature, signature;~~ an encrypted signature private key which is formed by encrypting a signature private key for writing the signature by use of a public key of a changing right ~~holder, holder;~~ and a signature written by use of the signature private key on desired data included in the lock data.

[0023] Further, according to the present invention, ~~in~~ the method for changing lock data, ~~executes~~ a step ~~for~~ of storing lock data including a first public key, an encrypted private key formed by encrypting a private key corresponding to the first public key by use of a common ~~key, key;~~ a plurality of encrypted common keys formed by encrypting the common key by use of public keys of respective ~~group/members, group members;~~ a second public key for verifying a signature, an encrypted signature private key formed by encrypting a signature private key for writing the signature by use of a public key of a changing right holder, the first public key, the encrypted private key, the encrypted common key, the second public key, and a signature written by use of the signature private key on the encrypted signature private key, a step ~~for~~ of decrypting the encrypted signature private key included in the lock data by use of the private key of a changing right holder, a step ~~for~~ of changing the lock data, and a step for writing a signature on the changed lock data by use of the signature private ~~key key.~~ is executed.

[0024] In this structure, because only the changing right holder, and ~~only~~ additionally the member who generates the lock data, can acquire the signature private ~~key,~~ key in the case that the signature is successfully verified on the lock data after the change, it is then confirmed that the lock data is changed by the changing right holder.

[0025] In an alternate embodiment, ~~Further in this structure,~~ the step ~~for~~ of changing the above-mentioned lock data ~~may be structured so as to~~ may include a step ~~for~~ of changing the second public key, a step ~~for~~ of changing the signature private key, a step ~~for~~ of changing the encrypted signature private key before changing by use of a new encrypted signature private key newly formed by encrypting a changed signature private key by use of the public key of a changing right holder, and a step ~~for~~ of writing a signature by use of the

signature private key after changing. In this case, the changing right holder can set a changing right holder by setting a new signature public key and private key.

[0026] The above-mentioned lock data may include a version identifier for indicating the version of the above-mentioned lock data. The above-mentioned lock data may include a precedent version dealing identifier to control how to deal with the lock data of the precedent version based on the identifier. The above-mentioned precedent version dealing identifier may be generated based on the change content of the above-mentioned lock data. ~~Further~~ Further, the above-mentioned precedent version dealing identifier may include the information for identifying whether the change of the above-mentioned lock data should be applied retroactively or not.

[0027] The present invention may be realized as hardware or may be realized at least partially as software. In the case of software, it can be installed in a computer system by way of a communication medium or software package (recording medium).

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] FIG. 1 is a diagram for illustrating a calculation rule for determining the trust level of the complex lock.

[0029] FIG. 2 is a diagram for illustrating a calculation rule for determining the trust level of others based on the trust level in the trust body and the trust level of the trust body in others.

[0030] FIG. 3 is a structural diagram for illustrating the outline of the whole cryptography system of the present invention.

[0031] FIG. 4 is a diagram for illustrating the structure of the group lock of the present invention.

[0032] FIG. 5 is a diagram for illustrating the structure of the public lock list of the present invention.

[0033] FIG. 6 is a diagram for illustrating the structure of the private lock list of the present invention.

[0034] FIG. 7 is a diagram for illustrating the structure of the cryptography of the present invention.

[0035] FIG. 8 is a flowchart for describing the group lock generation flow of the present invention.

[0036] FIG. 9 is a flowchart for describing the flow for addition to a lock list of the present invention.

[0037] FIG. 10 is a flowchart for describing the flow for judgement of usability of a private lock of the present invention.

[0038] FIG. 11 is a flowchart for describing the encryption flow of the present invention.

[0039] FIG. 12 is a flowchart for describing the decryptability judgement flow of the present invention.

[0040] FIG. 13 is a flowchart for describing the flow for acquiring a private key in a private lock list of the present invention.

[0041] FIG. 14 is a flowchart for describing the decryption flow of the present invention.

[0042] FIG. 15 is a flowchart for describing the signature confirming flow of the present invention.

[0043] FIG. 16 is a flowchart (1) for describing the group lock changing flow of the present invention.

[0044] FIG. 17 is a flowchart (2) for describing the group lock changing flow of the present invention.

[0045] FIG. 18 is a diagram for illustrating a system to which the present invention is applied.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0046] First ~~the~~ a general outline of the present invention ~~will be~~ is described below. A set of individuals is referred to as a group and an individual ~~namely a~~ or member, who is a component of a group, is referred to as a member hereinafter. The present invention is a public key cryptography system to which the concept of group is introduced. In other words, the present invention is a cryptography system incorporated with two main functions including the encryption ~~function~~ function, for enabling an arbitrary member who belongs to a specific group to decrypt the ~~cryptography~~ cryptography, and the signature function for enabling an arbitrary member who belongs to a specific group to write a signature. The present invention is advantageous in that the member who has written the signature is not ~~clarified~~ identified but only the fact that ~~some one~~ someone who belongs to the group has written the signature ~~is clarified~~ is identified because a signature ~~can be~~ is written by use of the group private key.

[0047] A pair of keys, a private key and a public ~~key~~ key, corresponding to a group is are provided, and ~~these keys~~ are referred to as group private key and group public key

respectively. ~~Further~~ Further, a common key (symmetric cryptography key) for encrypting the group cryptography key is provided. A group private key is encrypted by use of a common key, and the common key is encrypted by use of an individual public ~~keys~~ key of all the members, ~~and thereby forming a set of encrypted common keys is formed.~~ keys. The set of the encrypted common keys and the encrypted group private key are made available at least for the respective ~~members.~~ members of the group. An arbitrary member ~~who belongs to~~ of the group can decrypt the common key (which has encrypted by use of the corresponding individual public key) by use of the individual private key of the member itself, and further can decrypt the group private key by use of the decrypted common key, in other words can acquire the group private key. As described ~~herein~~ above, an arbitrary information is encrypted by use of the group public key, and then an arbitrary member of the group can decrypt the encrypted information by use of the group private key acquired as described ~~herein~~ above. ~~Similarly~~ Similarly, a member of the group can write a signature by use of the group private key.

[0048] The generation of a pair of the group private key and the group public key which are necessary to ~~realize~~ implement these functions, the generation of the common key, encryption processing by use of the group public key, and ~~processing the process~~ for changing the member of the group such as adding or deleting of the ~~member~~ member, are described ~~hereinafter.~~ below.

[0049] To maintain the confidentiality of information by means of encryption of the information, the location of the encrypted information itself is ~~not questioned,~~ known, in other words, is not ~~clarified~~ identified. ~~This concept means that~~ Thus, a mechanism for re-encrypting ~~for some reason~~ the information, for any reason, which has been encrypted previously cannot be ~~accepted~~ used. The reason is that it is difficult to specify the location of the information ~~which is wanted to be re-encrypted because the location is not questioned.~~ known. Therefore, when a member ~~who is of~~ a group ~~component~~ is changed, the already encrypted information is not ~~re-encrypted~~ re-encrypted, but instead a new key is ~~generated~~ generated. ~~instead.~~ generated. In the conventional public key cryptography system ~~which is used in individual unit~~, an individual who has his or her own corresponding ~~is an everlasting existence and the key~~ key, are in the relation of one-to-one correspondence and renewal of the group key is not ~~necessary,~~ necessary. ~~however~~ However, the renewal of it is necessary to renew the key ~~is necessary~~ for changing the component of the group because of the ~~correspondent relation~~ relationship between group and the key key corresponds to the individual member.

[0050] ~~In the~~ The present invention provides an effective means for providing a cryptography and signature system ~~of the present invention, an effective function not only~~ in the case of the above-mentioned encryption and writing signature in group ~~units~~ units, but also in the case that a ~~key~~ key, corresponding to a ~~role of an individual engaged in a position~~ for taking a specific role in an organization such as the chief of personnel department in a ~~company~~ company, is provided. For example, there is a key corresponding to the ~~role~~ position of the chief of personnel department, when the individual who is engaged in the chief of personnel department is changed, it is possible to accommodate the change in the real world by changing the key corresponding to the ~~role~~ position of the chief of personnel department. A member who wants to send an encrypted document to the chief of personnel department may encrypt the document by use of the public key corresponding to the conventional key for this ~~role~~ position (chief of personnel department). The new or subsequent chief of personnel department can check the encrypted information by use of the public key corresponding to the former ~~role~~ position in the past without changing the information which has been ~~encrypted already~~ already encrypted.

[0051] In a group having a purpose such as a project group in a company, the work based on cooperative work and ~~roles participated by~~ the positions of a plurality of members is important, and the members of the cooperative working group or individuals who are taking a ~~role~~ position are not fixed. Therefore, ~~the more~~ strict confidentiality between the inside and outside of the group is required.

[0052] Recently, the system for giving assurance of a certain level to the public ~~key~~ key, called as authentication ~~office~~ office, in the information network service has been popularly used, it is possible to exclude vitiated keys by use of an authentication office in the present invention.

[0053] Next, respective components of the present invention ~~is~~ are described. The respective components described ~~herein under~~ below are described.

- (1) Complex lock
- (2) Group lock
- (3) Individual lock
- (4) Private key of an individual lock
- (5) Complex lock list
- (6) Trust body
- (7) Authentication office

(1) Complex lock

[0054] The complex lock is a generic name of the lock for realizing the group lock (role lock) and individual lock described hereinafter, and in detail the electronic data having components described herein under.

a. Name

[0055] A name is a character string for indicating an substrate in the real world corresponding to a complex lock which a person can read, and takes a role as a an identifier of the complex lock. It is not desirable to use a space or confusable character string so that a person does not recognize confusingly different character strings as the same character string.

b. Forming date and forming personnel.

[0056] The forming date and forming personnel are the date when the complex lock is formed and the personnel who forms the complex lock. The forming personnel writes a signature on all the formed complex locks. The signature procedure includes encryption of the electronic data which constitutes the complex lock by use of the individual key of the forming personnel.

c. A private key which is encrypted by use of the common key

[0057] This is the encrypted key which is formed by encrypting the private key of the decrypting lock by use of the common key.

d. List of common key

[0058] The list of common key is a list formed by a method in which the common key formed by encrypting the private key of the common lock is encrypted by use of the public key of the member and the name of the member (any data for identifying the member may be used) is given as a label. The common key can be decrypted by ~~decrypting~~ by use of the private key of the member, and further as the result, the private key of the complex lock is decrypted to acquire. A cryptography sent from others can be decrypted by use of the private key of the complex lock.

e. Public key

[0059] The public key is the public key of the complex lock. The data is converted to cryptography by use of the public key when the information is encrypted.

f. Private lock list of changing lock.

[0060] A first pair of a public key and a private key is required for controlling the changing right of the complex lock ~~is required independently independent from~~ of the a second pair of the public key and the private key used for maintaining the confidentiality of

the information. This first pair is referred to as changing lock. The complex lock holds the list formed by a process in which the private key of the changing lock is encrypted by use of the public key of the changing right holder and the name of the changing right holder is given as a label. Only the changing right holder of the complex lock is allowed to form a complex lock of a new version by changing the complex lock, for example, by adding or deleting a member. The changing right holder is ~~designated previously~~ previously designated. When a complex lock is changed by a changing right holder and changed to a new version, the complex lock can be set automatically so that a person who trusts the old version can trust the new version. This is referred to as an automatic trusting mechanism. The trust of the lock will be described ~~hereinafter~~ below. To clarify that the complex lock is changed by a proper changing right holder, a signature is written by use of the private key of the changed lock when the complex lock is changed. However, if all members of the complex lock have the changing right of the complex ~~lock~~ lock, a pair for maintaining confidentiality is used. In this case, the signature is written by use of the private key of the current version.

g. Public key of changed lock.

[0061] The public key of the changed lock is the counter part of the private key of the above-mentioned changed lock ~~for constituting together~~ and forms a pair, and used for decryption of the complex lock with signature by use of the above-mentioned private key of the changed lock, it may be possible to confirm the signature. In addition, the ~~term-period~~ term-period of validity of the complex key or the ~~term-period~~ term-period of validity during the off-line period when the authentication office is not available for communication is added to control the use of the complex lock.

(2) Group lock

[0062] The group lock is the complex lock ~~corresponding that~~ corresponds to the group of the real world. The group includes a plurality of members generally. The group lock also functions ~~also~~ as the role lock (for example, chief of personnel department).

(3) Individual lock

[0063] The individual lock is a complex lock ~~corresponding that~~ corresponds to an individual. The individual lock is realized by means of the complex lock. A member of the complex lock as the individual lock specifies a trustee. The trustee means a person other than the individual to whom the same right as the individual has is given with conditions. This system allows the trustee who can take a role as an alternative to the individual to decrypt the information when the individual forgets the pass phrase. For example, the individual lock is

provided to avoid the risk caused by depending on one individual to keep the confidentiality of information and to decrypt information in the company. Further the individual lock can be used to audit or censor the information. It may be possible to set the condition that the approval of a plurality of specified trustees is required for the trustee to use the individual lock.

(4) Private key of the individual lock

[0064] The private key of the individual lock is protected so as to be only accessed by ~~only~~ the user. For example, the private key is protected by the common key cryptography technique in which a pass phrase known only by the individual (user) is used as the key for decrypting the cryptography. Otherwise, the private key may be protected by a method in which the private key of the individual lock is stored in a special device (IC card, PDA (Personal Digital Assist)), which the user ~~can carry~~ always carries, and it is taken out when it is required. ~~Further otherwise, In addition,~~ the private key may be protected by a method in which the physical and bodily feature of the user (finger print, voice print, eyeground neurolemma pattern, and the like) is detected for identification. ~~Yet otherwise, Alternately,~~ the private key may be protected by a method in which the feature of a signature is detected for identification. Other various access control methods may be employed. As described ~~herein~~-above, only the user can get the private key when it is necessary.

(5) Complex lock list

[0065] The complex lock list means the complex lock list in which the trustability of individuals ~~are~~ is clarified. The complex lock and the corresponding trustability are maintained in the form of a pair. An individual is judged depending on the trustability in the list when the complex lock is used. The trustability of the complex lock which is not listed in the list is interpreted to be unclear. For example, the complex lock list is used when an individual or a group group, who is allowed to decrypt the cryptography is specified in the complex lock list list, to get the public key from the corresponding complex lock and an encrypted private key is generated. In other words, the complex lock list is a public lock list in which the public key of trusted individuals and groups is registered ~~indirectly, therefore indirectly therefore,~~ the complex lock list may be a public lock list in which the public key keys of individuals or groups are registered directly. The complex lock itself may be a complex lock which is stored in an apparatus located far apart for reference in addition to the complex lock stored in an apparatus located here, and otherwise the complex locks stored in this apparatus and the outside this apparatus are used ~~mixedly~~ interchangeably.

(6) Trust body

[0066] In the present invention, the complex lock used in a group can be generated by anyone, but cannot be an effective key without a level of trust. The trust of the complex lock means that the actual correspondence between the group (including role or position) which is existing as a substance in the real world and the complex lock which ~~is expected to be correspondent~~ corresponds to the group, is trusted. In detail, ~~not only both the correspondent relation~~ relationship between the group and the complex lock ~~but also~~ and the coincidence between the member of the group in the real world at the time point of trusting and the member included in the complex lock ~~is~~ are required. For example, it is assumed that there is a complex lock having the name "Personnel Department, First Section". It may be possible that a group in the real world having the name "Personnel Department, Personnel Section" exists, but a group in the real world having the name "Personnel Department, First Section" does not exist. It may be also possible that though a group in the real world having the name "Personnel Department, First Section" exists, a corresponding proper complex lock does not exist. Therefore, a complex lock cannot be trusted based on only the name of the complex lock. Also a complex lock cannot be trusted in the case that, though some members in "Personnel Department, First Section" have been changed, such changed members remain in the member of the complex lock.

[0067] The information which describes trustability of the complex lock is referred to as trust information. The information which describes the trustability of the trust information itself is also included in the trust information. The main body which holds the trust information is referred to as the trust body. Trusting the trust information and the complex lock based on what reason is dependent on the trust body. The trust body is classified into two types, namely individual and authentication office which will be described in (7) hereinafter. A trust body can trust other trust bodies. In ~~such~~ such a case, a trust body who is ~~trusted~~ trusted, is referred to as ~~as~~ a trusted body. A trust body uses the complex lock only when the complex lock is trusted. When a trust body does not have the direct trust information on the complex lock, it may be possible that the trust body can trust the complex lock if another trust body which is trusted by the trust body trusts the complex lock.

[0068] For example, it is assumed that there is an individual "Mr. Tanake" and an authentication office "X Trading Company" as the trust body. They are in the relation that the individual "Mr. Tanaka" trusts automatically any complex lock as long as the authentication office "X Trading Company" trusts it if the individual "Mr. Tanaka" trusts the authentication office "X Trading Company", but on the other hand, the authentication office "X Trading

Company" does not necessarily trust the complex lock which the individual "Mr. Tanaka" trusts.

[0069] The degree of trustability is ~~rated~~grouped into ratings, and the rating is referred to as trust level. It is possible to obtain the trustability of a complex lock having unknown trustability by calculation using the trust level. The trust level used at that time is, for example, an exemplary table of trust level shown herein under.

[Table 1]

Level \odot : fully trust

Level \circ : sufficiently trust

Level Δ : somewhat trust

Level $?$: unknown

Level \times : not trust

[0070] FIG. 1 shows an example in which the trust level of a complex lock having the unknown trust level is obtained from the trust level of complex locks of two different trust bodies, for example, two different individuals A and B, which are independent from the same complex lock. The first row in FIG. 1 shows the trust level of the individual A and the left column in FIG. 1 shows the trust level of the individual B, and the result is shown in the form of table. For example, if the trust level set on the individual A is \odot is " \circ " and the trust level set on the individual B is $?$, is " $?$ ", then the trust level of the complex lock is \odot , is " \circ ".

[0071] For example, the calculation rule as shown in FIG. 2 is used for calculation of the trust level in which the trust level in this trust body and the trust level in another trust body of this trust body or the trust level in the complex lock are used. The first row in FIG. 2 shows the trust level in this trust body and the left column in FIG. 2 shows the trust level in another trust body of this trust body or the trust level in the complex lock, and the result is shown in the form of ~~table~~tables. For example, if the trust level in this trust body is \odot is " \circ " and the trust level set by this trust level is $?$ is " $?$ ", then the trust level of the complex lock is $?$, is " $?$ ". As described ~~herein~~ above, it is possible to determine the trustability of a trust body having the unknown trustability or complex lock by use of the calculation rule shown in FIG. 1 or FIG. 2.

(7) Authentication office

[0072] The authentication office is one of trust bodies as described ~~herein~~ above. The function provided by the authentication office is to express or provide the public trust in the unit like an company or organization, where, for example, some cryptography system is

used. The trust criterion of the complex lock in the authentication office is determined arbitrarily by a company or an organization which operates this authentication office. Several methods as described ~~herein under below~~ are available as the method for determining the trust criterion. In the following description, "to guarantee" means the action that an individual other than the ~~registrant-registrant~~, certifies the validity of the complex lock to be registered.

[0073] a) The validity is confirmed by means of any procedure performed by a specific manager of the authentication office. When the validity is confirmed, the authentication office trusts the complex lock. Any procedure described herein above means arbitrary procedure in the real world. For example, any procedure includes ~~finger-print~~ fingerprint put on the application form or confirmation procedure by means of an identification paper or card of the applicant. Otherwise, the complex lock may be trusted for registration by means of various ways, for example, duplicated confirmation of the name, guarantee by other specific individual indicated for each registrant, guarantee by guarantors in a prescribed number, or signatures of individuals whom the authentication office trusts in a prescribed number determined previously.

Example

[0074] An example of the cryptography system which uses the group lock is described ~~hereinafter, below~~. A case in which the group lock in the complex lock as described ~~hereinbefore above~~ is used ~~used~~, is described ~~hereinafter, below~~, and in the case that the other type of the complex ~~lock-lock~~, namely the individual ~~lock-lock~~, is ~~used, used~~, ~~similarly~~ Similarly the cryptography system is structured with the same structure and the same manner ~~excepting except~~ that the member in the group lock is changed to the trustee in the individual lock. The ~~above-mentioned before-mentioned~~ role lock is included in the special application of the group lock, to make the function of the group lock effective as the role lock, the number of members of the group lock is ~~set 1-set to 1~~, and the individual who is engaged in the role currently may be assigned as the only member. It may be possible to operate the group lock in which the member of the role lock of the vice-president includes a secretary in addition to the vice-president himself.

[0075] Each member who uses the cryptography system of the present invention holds two lock lists. In detail, a) "public lock list" namely the list of the group lock which respective members trust and the individual lock, and b) "private lock list" namely the list of the group lock from which each member can acquires directly or indirectly the private key based on the private key of the member itself. For the purpose of simplicity, it is assumed

that the group and individual lock included in the "public lock list" are trusted, and the medium trust level such as "somewhat trust" is not ~~given~~ used. Whether it is trusted or not is determined based on the above-mentioned calculation rule of degree of trustability or based on the judgement ~~by of a user, user, and the~~ The detailed description in the example is omitted. However, it is assumed that the group lock, after a change is trusted automatically in the case ~~that~~ when an automatic trust mechanism, in which the group lock used just before the change is trusted when the group lock is changed is ~~in function~~ functioning, ~~namely in the case that the group lock used before the change is trusted.~~ The registration procedure to the above-mentioned authentication office is not described ~~directly hereinafter~~ below in the example, in the case that there is the authentication office in a network as described ~~herein~~ above, the lock which is generated or changed is registered to the authentication office. However, this registration procedure is not sine qua non of the present invention.

[0076] ~~First~~ First, the whole structure of the example is described with reference to FIG. 3. The basic function of the present example is to transmit the information correctly and confidentially from an individual to another individual. The individual may belong to a group. The information may be transmitted by means of direct transmission such as mail or indirect transmission through a file service.

[0077] Not only the cryptography but also the individual public key or group lock is transmitted between individuals as shown in FIG. 3 as required. In the case that the judgment to determine whether the individual public key and group lock properly correspond to the individual and group which exist in the real world is required, it is necessary to establish a judgement procedure.

[0078] When a plain document in "individual" shown in FIG. 3 is encrypted to a cryptographic document, a lock corresponding to the lock which an individual or a group who is to be allowed to decrypt the cryptographic document holds is selected from the lock list for encryption. The cryptogram which the selected individual or an individual who belongs to the selected group can decrypt is thereby generated. Otherwise, a plain document is decrypted by means of a common key K_A , and a lock corresponding to the lock which an individual or a group who is to be allowed to decrypt the decrypting key K_B required to decrypt the cryptography holds is selected from the lock list, and the selected lock is encrypted and transmitted.

[0079] When the transmitted encrypted information is decrypted, the encrypted information is decrypted by use of the individual private key of the individual if the obtained

cryptographic information can be directly decrypted by use of the individual private key of the individual. If the obtained cryptographic information can be decrypted by use of the group lock to which the individual belongs indirectly or directly, the group lock is converted to the group private key by use of the individual private key of the individual to obtain the group private key, and the cryptographic information is decrypted by use of the group private key. The group private key is discarded just after it is used, and the individual does not hold it. In this system, only the individual private key is required for "individual" to keep it confidential. In the case that the cryptographic information is decrypted by use of the common key KA, first the decrypting key KB which is necessary for decryption is decrypted by use of the individual private key of the individual. If the cryptographic information can be decrypted by use of the group to which the individual belongs, the group lock is converted to the group private key by use of the individual private key of the individual to obtain the group private key, and the decrypting key KB is acquired by use of the group private key and the cryptographic information is decrypted to a plain document by use of the decrypting key KB.

[Group lock]

[0080] The structure of the group lock in the present example is shown in FIG. 4. Reference characters shown in FIG. 4 are described ~~herein under~~ below.

L_G : the label of this group lock.

[0081] The label is a character string. ~~The duplication~~ Duplication is not allowed in a lock list of an individual. The label is not used as an identifier because duplication may occur as a whole. As the public key is not coincident unless the label is coincident, as a result the processing can be performed faster ~~resultantly~~.

P_G : the public key of this group lock

[0082] The public key of this group key is a public key corresponding to the public key cryptography system to be used, and this is generally a data string having a fixed length consisting of 512 bits to 2048 bits. When a plain document is encrypted so that all individuals who belong directly or indirectly to this group can decrypt the encrypted document, this public key is used for encryption. Further, when the information with a signature of an arbitrary individual who belongs directly or indirectly to this group is to be confirmed, the signature is confirmed by use of this public key. The public key is included in the group lock as it is, and any individual can check the public key.

S_G : Private key of this group

[0083] The private key of this group is a private key corresponding to the public key cryptography system ~~which is being~~ used, and generally a data string having a fixed length consisting of 512 bits to 2048 bits. The private key of this group is used when a cryptogram encrypted by use of the corresponding public key is decrypted. The private key of this group is used also when an arbitrary individual who belongs directly or indirectly to this group writes a signature as an individual of this group. The private key is a key which is encrypted ~~combinedly~~ by use of the private key of an individual and the common key directly or indirectly, and when the private key is used, first the common key is decrypted by use of the private key of the individual and the private key of the group lock is thereafter decrypted for acquiring. The private key of the group lock is discarded just after use ~~and is not held alone~~.

C_G : Common key for encrypting the private key of the group lock

[0084] This key is the common key, and a known key such as DES, FEAL, or the like may be used. The size of the key consists generally of 40 bits to 128 bits.

$C_G(S_G)$: Private key of the group lock encrypted by use of the common key C_G

[0085] This key is a cryptogram which is formed by encrypting the private key S_G of the group lock by use of the common key. The common key C_G is necessary to acquire the private key S_G .

M_i : Member of this group

[0086] M_i is the existence in concept, and does not appear in the data structure directly. A member may be an individual or a group. As described hereinbefore, in the case of an individual key instead of a group key, the member means the trustee.

P_U : Public key for changing this group lock

[0087] This key is a public key corresponding to the public key cryptography system ~~which is being~~ used, and is generally a data string consisting of 512 bits to 2048 bits. It is required that the group adds or deletes the member. As the method for identifying the person who has the right to perform such change, a pair of an exclusive public key and private key is used. This key is such public key. The group key includes the private key for changing which has been decrypted directly or indirectly by use of the individual private key ~~that belonging to the individual having the changing right has right~~. When the group lock is changed, the new group lock is signed by use of the private key for changing. Because only the changing right holder can have the private key for changing, the signature validates that the change has been done by a proper changing right holder. The validation is processed

automatically if the previous group key is trusted. ~~Any one~~ Anyone can ~~refers~~ refer to this public key for changing because the public key for changing is included in the form as it is.

S_U : Private key for changing this group lock

[0088] This key is a private key corresponding to the public key cryptography system ~~which is~~ being used, and is generally a data string of fixed length consisting of 512 bits to 2048 bits. The function is the same as that described for P_U .

C_U : Common key for encrypting the private key S_U for changing the group lock.

[0089] This key is a conventional common ~~key, a key.~~ A known key such as DES, FEAL, or the like may be used. The size of a key is generally 40 bits to 128 bits.

$C_U(S_U)$: Private key for changing the group lock which has been encrypted by use of the common key C_U .

[0090] This key is a cryptogram which has been formed by encrypting the private key S_U for changing the group lock. The common key C_U is necessary to obtain the private key S_U .

V : Version number of this group lock

[0091] V is a natural number. V is 1 when a new group lock is generated. V indicates the version of the group lock. When the group lock is changed, the version number is added 1 on the reference version number.

F : Value indicating processing of immediately precedent ~~version~~ version.

[0092] F is any one of "unnecessary", "necessary", and "deletion". When the group lock is changed, an individual who has the immediately precedent ~~version~~ version, is required to deal the immediately precedent version properly because the individual has the new version. The value "unnecessary" means that the immediately precedent version is unnecessary. The value "necessary" means that the immediately precedent version is necessary to validate the signature written by use of the immediately precedent version to decrypt a cryptogram formed by use of the immediately precedent version. In this case, the new version should be used for new encryption and signature. The value "delete" is approximately equal to "unnecessary", and means that the immediately precedent version should be deleted when the individual cannot acquire the private key of the new version. When a group lock is ~~generated newly,~~ newly generated, this value is meaningless.

U_i : Changing right holder of this group

[0093] U_i is a conceptual existence and does not appear on the data structure. The changing right holder is assigned to an individual or a group.

L_m : Label of M_i

[0094] L_m is a label character string. This label is the label of a group lock of ~~either~~ another group or individual key who is a direct member of this group lock. Though the individual lock is not described in the present example, the individual lock consists of a private key which is managed by the corresponding individual and a public key which is open, and a label is not given at least to the public key.

P_{M_i} : Public key of M_i

[0095] P_{M_i} is a public key corresponding to the public key cryptography system which is used, and is generally a data string of fixed length consisting of 512 bits to 2048 bits. The public key of the direct member of this group.

$P_{M_i}(C_G)$: C_G encrypted by use of P_{M_i}

[0096] P_{M_i} is obtained by encrypting C_G by encryption processing corresponding to the public key cryptography system which is used. To acquire C_G by use of P_{M_i} , the private key ~~S_{M_i}~~ S_{M_i} corresponding to P_{M_i} is necessary. This is held by means ~~of~~ of an arrangement which uses the corresponding L_m as an index.

L_{U_i} : Label of U_i

[0097] This is a label character string of U_i . This is the label of the individual lock of the individual who is the changing right holder of this group lock.

P_{U_i} : Public key of U_i

[0098] This is the public key corresponding to the public key cryptography system ~~which is being~~ used, and is generally a data string of a fixed length consisting of 512 bits to 2048 bits. This is the public key of the individual who is the changing right holder of this group lock or the public key of the group lock.

$P_{U_i}(C_U)$: C_U encrypted by use of the public key of U_i

[0099] This is obtained by encrypting C_U by means of encryption processing corresponding to the public key cryptography system which is used. To acquire C_U by use of this P_{U_i} , the private key S_{U_i} corresponding to ~~P_{U_i}~~ P_{U_i} is necessary. This is held by means ~~of~~ of an arrangement which uses the corresponding L_{U_i} as an index. In the present example, the private key is added with the information to identify the data and then encrypted like the packet data structure in the packet communication. Therefore, whether the private key is normally decrypted or ~~not~~ not, can be judged easily based on the additional information when the encrypted private key is decrypted.

Sig (S_U) : Signature by S_U for the whole.

[0100] This is a data string for indicating a signature. Herein, the whole means L_G , P_G , $C_G(S_G)$, V , F , P_U , $C_U(S_U)$, L_{Mi} , $P_{Mi}(C_G)$, L_{Ui} , and $P_{Ui}(C_U)$. Signature means encryption processing by use of the private key S_U . In the public key cryptography system, conversely as opposed to the normal system, the data is encrypted by use of the private key and the encrypted data can be decrypted by use of the public key. Because the data must be encrypted by use of the private key in order to decrypt it by use of the public key, it is confirmed that the signature is written by use of the private key by confirming decryption by use of the public key. Actually, the message digest is applied to the target range and a signature is ~~put on the processing result~~ processed by use of the private key S_U . The message digest ~~means a processing means~~, which is a process in which the information consisting of about 128 bits, depending on the content of the target range, is generated regardless of the size of the target range because the encryption of the entire target range of the signature requires high cost. A disclosed message digest processing algorithm is used and a key is not used. For confirmation, the encrypted target data is subjected to message digest, and whether the signature and the decrypted result are coincident or not is confirmed. The message digest processing is a ~~processing process~~ similar to the check sum, and on the other hand by using the direction function in the ~~processing process~~, it is made difficult to forge the input data which generates the same result. Further, because the size of the generated data is large, it is difficult to forge the data as a round robin. The name "Message digest" is a generally known name in the cryptography related field, and ~~the~~ a well known system. It is assumed that the message digest processing function is f_{Md} , the complex operation of the target data is expressed by arithmetic sum, and the signature written by use of S_U is expressed by a function S_U , then $Sig(S_U)$ is obtained as the result of the following processing.

[Expression 1]

$$S_U (f_{Md} (L_G + P_G + C_G(S_G) + P_U + C_U(S_U)$$

n

$$+ \sum_{i=1}^n (L_{Mi} + P_{Mi}(S_G) + L_{Ui} + P_{Ui}(S_U)))$$

$i=1$

S_U' : S_U of the precedent version

[0101] This is a private key corresponding to the public key cryptography system ~~which is being~~ used, and is generally a data string of fixed length consisting of 512 bits to 2048 bits. This is the private key for changing the immediately precedent version. This functions similarly to S_U (in detail, refer to the description of P_U).

Sig (S_U') : Signature by use of S_U' for the ~~whole~~ whole.

[0102] This is a data string which indicates a signature. Herein the whole means L_G, P_G, C_G (S_G), V, F, P_U, C_U (S_U), L_{Mi}, P_{Mi} (C_G), L_{Ui}, P_{Ui} (C_U), and Sig (S_U). This is not given when this is generated newly. Sig. (S_U') is expressed as described herein under similarly to the Sig (S_U).

[Expression 2]

$$S_U (f_{Md}(L_G + P_G + C_G(S_G) + P_U + C_U(S_U)) \\ n \\ + \sum_{i=1} (L_{Mi} + P_{Mi}(C_G) + L_{Ui} + P_{Ui}(C_U) + \text{Sig}(S_U))))$$

[0103] In the present example, the signature covers the whole data, however the signature may partially cover the data which is wanted to be prevented from ~~forging~~ forgery.

[Public lock list]

[0104] FIG. 5 shows the structure of the public lock list in the present example. The public lock list is owned independently by individuals, the group lock and the individual lock which the individual ~~trusts~~ trusts, is held by the arrangement having the label of the lock as an index.

[0105] As shown in FIG. 5, the public lock list consists of G_i (trusted group lock), L_{Gi} (label of the group lock G_i), I_i (public key of trusted individual), and L_{Ii} (label corresponding to the public key I_i of the individual).

[0106] The judgement of the trustability of the lock ~~which~~ is required when a new data is added to the public lock list relied on the public lock list holder in the present example. However, the subsequent version of the group lock which has been trusted is subjected to automatic trusting. Otherwise, it is possible to determine the trustable lock or trust body by means of the calculation rule associated with the above-mentioned trust level. In this case, the trust level can be determined surely and easily by using the trust relation registered in the above-mentioned authentication office.

[0107] A decryptable group or individual is designated for encryption, at that time, and at least one or more corresponding group locks or individual locks are selected from the public lock list for designation.

[0108] When the validity of the signature is confirmed, the public key corresponding to the private key which has been used for writing the ~~signature~~ signature, is taken out from the public lock list for using.

[Private lock list]

[0109] The structure of the private lock list in the present example is shown in FIG. 6. The private lock list is owned independently by individuals, and holds the group lock by which the individual can acquire the private key in the form of an arrangement having the label of the group lock as an index. The private key is acquired by directly or indirectly by applying the individual private key of the individual to the group lock.

[0110] As shown in FIG. 6, the private lock list consists of G_i (group lock which is used with using the private key) and L_{G_i} (label of the group lock G_i).

[0111] If the group private key in the internal of the group lock can be acquired by directly or indirectly by applying the individual private key of the individual in the ~~processing process~~, to add the group lock to the public lock list, addition to the private lock list is performed when added. Therefore, it is not necessary for the user to be conscious of addition ~~processing process~~. It should be recognized that the fact that the group private key in the internal of the group is acquired by use of the individual private key of the ~~individual~~ individual, does not necessarily mean that the group key is trustable.

[0112] The judgement of the possibility of decryption is made faster by using the private lock list for decryption. Further, in the actual decryption processing, the private lock list is used for acquisition processing of the necessary group private key.

[0113] In writing a signature, the group private key in the private lock list other than the individual private key of the individual may be used for writing a signature. If a signature is written as described ~~herein~~ above, then the receiver who receives a cryptogram can identify the sender either an individual or group. Further, if the public key of the private lock used for the signature is attached together with the signature, the signature is validated easily and the receiver can validate the sender easily based on the public key without checking the signature.

[Cryptogram]

[0114] The structure of the cryptogram of the present example is shown in FIG. 7. In the present example, L_{M_i} of the group lock and the list of the paired P_{M_i} (S_G) have the same structure, and a cryptogram can be thereby decrypted by using any one of a plurality of private keys. As the result, when the information which is wanted to be disclosed to a plurality of members is encrypted, it is not necessarily required to form the group lock. In other words, a receiver group consisting of individuals and groups selected arbitrarily from the public lock list is temporarily formed. ~~formed temporarily~~.

[0115] The meaning of each character shown in FIG. 7 is described ~~herein~~
under below.

Pi : Decryptable group lock or public key of an individual

[0116] This is a public key corresponding to the public key cryptography system which is used, and is generally a data string of fixed length consisting of 512 bits to 2048 bits.

Li : Label of Pi

This is a label character string.

D : Plain document (information to be confidential)

This is an arbitrary character string.

K : Common key formed by encrypting the plain ~~document D~~ document D.

[0117] Because encrypting processing and decrypting processing are ~~slow~~ slow, due to the public key cryptography, the hybrid system in which a plain document is encrypted by means of common key cryptography and only the common key is encrypted by means of public key ~~cryptography~~ cryptography, is generally employed. The K is the common key. In the present example, K is encrypted respectively by use of K to thereby enable a plurality of groups or individuals to decrypt the encrypted document.

Pi (K) : K encrypted by use of Pi.

K (D) : D encrypted by use of ~~Pi~~ Pi.

S : Private key which a member who performs encryption processing can use

[0118] This is a private key used when a signature is given to a cryptogram. Any one of the individual private key of the individual and the private key of the group lock included in the private lock list is used.

P : Public key P which is paired with the private key S used for signature

[0119] The public key corresponding to the private key which the signer has used for signature according to the assertion is used when the signature is validated. It is held to specify the public key. If the public key is included in the public lock list of the receiver itself in the receiver side who has received the cryptogram, the receiver can validate that the signature written by a group or an individual who the receiver trusts is put, and the receiver can validate a sender individual or sender group who has transmitted the cryptogram.

Sig (S) : Signature by S for the ~~whole~~ whole.

[0120] This is a data string for indicating a signature. Herein, the whole means Li, Pi(K), and K(D). The signature is referred to the description of Sig (Su) in the structure of the

group lock. According to the same expression, Sig (S) is expressed as described ~~herein~~
~~under below.~~

[Expression 3]

$$S(f_{Md}(\sum_{i=1}^n (Li + Pi(K))D))$$

[Flow of processing]

[0121] Detailed process flow of the present example is described with reference to flowcharts shown in FIG. 8 to FIG. 16.

[Group lock generation]

[0122] The flowchart for describing group lock generation is shown in FIG. 8. It is required that the group lock or the public key of an individual corresponding to a member who is newly assigned, ~~assigned newly~~ is trusted by the generator when a group is generated (or when a group is added or changed). If the group lock or the public key of an individual corresponding to a member who is ~~assigned newly~~ newly assigned is not trusted, trusting namely addition to the lock list must be performed prior to the generation of the group key.

[0123] The generated group lock is added first to the lock list of the generator itself. The lock list is the generic name of the public lock list and the private lock list. Further, (when a cryptogram formed by encrypting for the generated group is decrypted, the member of the group needs the group lock. Conversely, when a cryptogram is formed for the group, also the group clock is needed. ~~Arbitrary~~ An arbitrary individual can encrypt. ~~Therefore~~ Therefore, it is necessary to distribute to individuals who may encrypt for the member or the group) the generated group lock is distributed to individuals who require it. Otherwise, the complex lock which is stored in the remote center may be sent when the sender of the cryptogram or the receiver requires it, or only the information which requires the complex lock may be sent. In the present example, the description of the distribution is omitted.

[0124] The flowchart shown in FIG. 8 is described in detail. The label of the group lock generated in step 101 is entered. In step 102, whether a lock having the same label as the input label exists in the lock list is tested. Generation of a lock having the duplicated label is refused, and if there is already a lock having the same label in the lock list, then the sequence proceeds to step 113, and generation of a group lock is stopped. On the other hand, if there is no lock having the same label, then the sequence proceeds to step 103.

[0125] In step 103 and step 104, a member M_i and a changing right holder U_i are designated. The member is a member who uses the cryptography system in which the group lock is used, and the changing right holder has the right to change the group lock, for example, to add or delete the member. The member and the changing right holder are not limited to an individual but may be a group, and designated by selecting one or more group locks or public keys of individuals from among the public lock list which the group lock generator has.

[0126] In step 105, a private key S_G , public key P_G , and common key C_G of the group to be ~~generated-generated~~, is generated. In step 106, the generated private key S_G is encrypted by use of the common key C_G to generate $C_G(S_G)$. Further, $P_{M_i}(C_G)$ which is formed by encrypting the common key C_G by use of public keys P_{M_i} of respective members M_i is generated, and each $P_{M_i}(C_G)$ corresponds to the label L_{M_i} .

[0127] In step 107, a changing private key S_U , changing public key P_U , and changing common key C_U of the group lock to be generated is generated. In step 108, the generated group lock changing private key S_U is encrypted by use of the common key C_U to generate $C_U(S_U)$. Further, the common key C_U is encrypted by use of the public key P_{U_i} of the changing right holder to generate $P_{U_i}(C_U)$, and each $P_{U_i}(C_U)$ corresponds to the label L_{U_i} .

[0128] In step 109, the version number of the group lock to be generated is set. In step 110, respective data of L_G , P_G , $C_G(S_G)$, P_U , $C_U(S_U)$, V , $P_{M_i}(C_G)$, and $P_{U_i}(C_U)$ are unified together. In step 111, a signature is written on the unified previous data by use of the changing private key S_U , that is, data conversion is performed. In step 112, the group lock is registered additionally to the lock list of the group lock generator and thus the generation of the group lock is brought to an end. The generated group lock has the structure shown in FIG. 4 as described ~~hereinbefore~~above.

[Addition to a lock list]

[0129] A ~~flow~~flowchart of the addition procedure to a lock list~~list~~is is shown in FIG. 9. Only the group lock or public key of the individual who is trustable is added to the lock list. This processing is used when the group lock which is generated or changed (generation of a new version) by ~~itself-itself~~itself, is added and when the group lock which is obtained from others is added.

[0130] In the present example, ~~processing-the process~~ associated with distribution such as distribution of a key by means of an authentication office and distribution of a key by way of e-mail or floppy ~~disc-disc~~disc, is not included. ~~Processing-The process~~ for calculating the

trustability of a key by calculating the trustability in a signer or the trustability in a key of a signer is omitted. It is possible to include the above-mentioned acquisition of the trust level obtained by calculation of the trustability and to use it to judge the trustability. In the present example, the automatic trusting procedure of a new version of a group lock which has been already trusted is shown. In the present example, a new version is automatically trusted only when it is validated that the new version is signed by use of the changing private key of the immediately precedent version.

[0131] In the addition to a private lock list, only the group lock from which the private key of the group lock can be acquired directly or indirectly by use of the individual private key of the individual itself from the trusted group locks is added.

[0132] The ~~flow-flowchart~~ shown in FIG. 9 is described in detail. In step 201, after a lock to be added is specified, the presence of a signature written by use of the changing private key S_U' of the immediately precedent version, trustability, and correctness of the signature are judged in steps 202, 203, and 204, and if any one of them is "YES", then the sequence proceeds to step 214, the ~~judgment-judgment~~, by the trust lock holder itself whether the lock to be added is trustable or ~~not-not~~, is entered. If the lock is trustable, the sequence proceeds to step 210, on the other hand if the lock is not trustable, the lock is not added to the lock list. In step 214 and step 215, the calculation to acquire the above-mentioned trustability can be used.

[0133] In steps 205 to 209, how to process the precedent version is determined. When an group lock of a new version is added, it is required to properly process the group lock of the precedent version. It is judged based on the F value included in the group key of the new version. A new encryption or writing a signature should not be performed regardless of F value because the precedent version is old. The public lock list and private lock list should be classified into the newest version and the ~~other-other version~~. In the present example, the classification is omitted, and only the newest is assigned when used. The processing which depends on F value is described ~~herein-under-below~~.

- a) In the case of $F = \text{"necessary"}$, group lock of old version is kept undeleted.
- b) In the case of $F = \text{"unnecessary"}$, group lock of old version is deleted.
- c) In the case of $F = \text{"delete"}$, group lock is kept undeleted if the individual itself can acquire a private key of the new version, and is deleted if otherwise.

[0134] In step 210 to 213, addition to the public lock list is performed, the usability of the private key of the lock to be added is judged, and if the usability is YES, addition is performed also to the private lock list.

[Judgement of the usability of the private lock]

[0135] A ~~flow~~-flowchart for judgement of the usability of the private key is shown in FIG. 10. In the processing, whether the encrypted private key included in an arbitrary group lock which is assigned can be acquired by directly or indirectly applying the individual private key of the individual itself is judged.

[0136] This processing is used to judge whether a group lock may be included in the private lock list (step 212 in FIG. 9). The same judgement as this processing is necessary to judge whether a group key is usable or not for decryption in other ~~situation~~-situations. ~~However~~-However, in many cases, simple processing to judge whether the group lock is included in the private lock list based on the fact that the group lock included in the private lock list is all the group lock from which the private key is acquired by the subject ~~itself~~itself, as long as ~~as~~as, it is known at the time point is used, and this processing is directly used not so often.

[0137] In the processing, first whether the private key of the group lock directly given by using the individual private key of the individual itself is judged. If the private key is not acquired, whether the private key of the group lock given by direct use of each group key in the private lock list of the subject itself can be acquired or not is judged. The processing may be performed according to this procedure for only the purpose of judgement because the private key of the group lock in the private lock list is already known to be usable.

[0138] The ~~flow~~-flowchart shown in FIG. 10 is described in detail. In step 301 the group lock being judged to be a-(judgement target) is assigned, in step 302 it is determined whether or not the individual lock of the individual itself is a member of the group lock is to be the judgement ~~target or not is judged~~-target, and if it is YES, it is judged to be usable. If it is not a member, in step 303 to step 305, the element Gi of the current private lock list is examined, and whether Gi is a member of the judgment target key or not is judged. In steps 303, 304, and 305, the process is repeated with incrementing i of Gi successively. In the repeating step, if any Gi is a member of the judgement target key, it is judged to be usable.

[Encryption]

[0139] The encryption processing flow of information is shown in FIG. 11. The following three items are entered in the processing.

- a) Plain document
- b) Decrypter

[0140] One or more decrypter is assigned from the newest group lock or individual public key included in the public lock list.

- c) Signer

[0141] Only one signer is assigned from the individual private key of the individual itself or newest group lock included in the private lock list. It is not necessary to assign unless a signature is written.

[0142] Signing means that the signature target data is subjected to message digest and the resultant signature block is signed by use of a private key. Signing by use of a private key means encryption by use of a private key. The paragraphs "cryptography" in data structure and Sig (S_U) in "group lock- in data structure should be referred for details.

[0143] The ~~flow~~-flowchart shown in FIG. 11 is described in detail. In step 401, the information D to be kept confidential is entered, and in step 402, one or more public key P_i corresponding to the newest group and individual which enables to ~~decrypt~~ decryption, is selected from the public lock list of the subject. In the ~~processing~~, process, a member who is enabled to decrypt the encrypted data is selected.

[0144] In step 403, the common key K is generated, and encryption of the information D by use of the key K is executed according to the public key cryptography system. In this case, the hybrid system in which the plain document is encrypted by use of the common key cryptography and only the common key is encrypted by use of the public key cryptography is employed because encryption processing and decryption processing using the public key cryptography is slow as described in the paragraph of [Cryptography]. The common key K is not necessarily the key which is generated every time when encryption is carried out, and may be the key which is generated as required or may be the fixed key which has been previously determined.

[0145] In step 404, K is encrypted by use of the public key P_i of each decrypter to generate $P_i(K)$, and the ~~label~~-corresponding label ~~respectively~~ is given. In step 405, whether the generated cryptogram is to be signed or not is judged, and if the judgement is NO, then summarizing of each data is executed in step 410, and the encryption processing is brought to an end. If the judgement is YES, the sequence proceeds to step 406.

[0146] Steps 406 to 409 are signature processing step, the data to be signed is subjected to message digest processing (step 406), a key to be used for signature is selected from the private lock list (step 407), signature is executed by use of the selected private key (step 406), and the arrangement K (D) and the signed message digest (=signature block) are combined together (step 409). The encryption processing is ~~ended though the above-mentioned steps. ended.~~

[Decryptability judgement]

[0147] A processing flow for judging whether an arbitrary cryptography can be decrypted by the subject itself or ~~not~~not, is shown in FIG. 12. For example, this ~~flow~~flowchart is used to confirm which encrypted file can be decrypted by the subject itself when the encrypted files are listed. This ~~flow~~flowchart is ~~processing a process~~ for executing the judgement of decryptability at high speed. In detail, ~~base~~based on the fact that decryption is impossible unless the label is coincident, first the coincidence of the label is confirmed and then decryption is tried only when the label is coincident. Generally, when the method for selecting the label is determined properly, this method provides sufficient performance. If the method for selecting the label cannot be specified, a method in which not only the label but also the public lock used for encryption is given to "cryptography" may be used for faster processing.

[0148] In the ~~processing, process~~, first the individual private key of the individual itself is tried to be used, and if decryption is impossible, then each group lock in the private lock list of the individual itself is tried to be used. Decryption described herein means decryption of only $P_i(K)$ corresponding to the label L_i in the "cryptography". It is not the purpose to obtain a plain document herein, $K(D)$ is not decrypted.

[0149] The decryptability judgment flow shown in FIG. 12 is described in detail. In step 501, a cryptography the decryptability of which is to be judged is assigned. In steps 502 and 503, whether the label in the cryptography L_i is coincident with the label of individual label of the individual itself is judged. If both labels are coincident each other, the sequence proceeds to step 509 to try decryption. If decryption is impossible in step 509 or if the coincident label cannot be found in steps 502 and 503, whether the label L_i in the cryptography is coincident with the owned private lock label or not is judged. If the coincident label L_{Gi} is found, then the sequence proceeds to step 511 to acquire the private key S_{Gi} of G_i corresponding to the label L_{Gi} , and decryption is tried in steps 512 and 513. If the decryption is not successful, the sequence proceeds to steps 506 and 507, and the

coincidence with the label of the private lock list owned by others and the coincidence with the label of the individual lock are tested. In step 506, the same processing as performed in step 504 is repeated for different labels, and in step 507, the same processing as performed in step 502 is repeated for different labels. If decryption is possible in step 510 or step 513, decryption in step 514 is judged to be possible.

[Acquisition of private key in group lock]

[0150] A flow for acquiring the private key S_G of the group lock included in the private lock list is shown in FIG. 13. The private key of the group lock is used for decryption and signature.

[0151] It is apparent that the private key can be acquired because only the group lock from which the private key is acquired by directly or indirectly applying the private key of the individual is included in the private lock list.

[0152] In the ~~processing~~, process, first direct application of the individual private key of the individual itself is tried. If the trial is not successful, application of the group lock in the private lock list is tried. In the trial application of the group lock, ~~the this processing process~~ is called recursively. A directed graph which is the inclusive relation between groups namely members formed as directed arc having the group as the node. Therefore, the private key is acquired in this ~~processing~~, process.

[0153] An acquisition ~~flow~~ flowchart of the private key S_{Gi} shown in FIG. 13 is described in detail. First in step 601, a group lock G_i in the private lock list is assigned. In step 602, whether the individual lock of the individual itself is included in the member of the group lock G_i is tested, and if it is included, the sequence proceeds to step 607, then the common key C_G is encrypted by use of the individual public key in the group lock G_i to extract the encrypted $P_{Mi}(C_G)$, and the extracted $P_{Mi}(C_G)$ is decrypted by use of the individual key to acquire the common key C_G . Further, $C_G(S_G)$ in the group lock is decrypted by use of the common key C_G to acquire the group private key S_G .

[0154] If the individual lock of the individual itself is not included in the member of the group lock G_i in step 602, then in steps 603 to 605 whether G_k is a member of G_i is tested on all the elements G_k of the private lock list. This ~~processing~~ process is performed to test whether each "the group lock G_k which the private lock can use" held by the subject itself is included as a member of the group lock G_i . If G_k , which is a member of the group lock G_i , is detected in step 604, then the private key S_{Gk} of G_k is acquired in step 608, the encrypted P_{Mi}

(S_G) in the group lock G_i is extracted in step 609, and the extracted $P_{G_i}(S_G)$ is decrypted by use of the private key S_{GK} to acquire the group private key S_G .

[Decryption]

[0155] A flow to decrypt an arbitrary cryptography is shown in FIG. 14. The ~~flow~~ flowchart shown in FIG. 14 is the almost same flow as shown for the above-mentioned "Decryptability judgment" ~~processing process~~. Steps 701 to 713 correspond to steps 501 to 513 in the decryptability judgment ~~flow~~ flowchart shown in FIG. 12. Only one exception is that $K(D)$ is decrypted by use of the key K of the common key cryptography to acquire the plain document D . In the case that the cryptogram has a signature, the signature is validated as ~~required-required~~, simultaneously when the plain document D is acquired.

[Signature validation]

[0156] A ~~flow~~ flowchart for validating a signature is shown in FIG. 15. The result obtained by ~~the process~~ processing in which the signature being validated (signature target) is subjected to a message digest process ~~processing~~ is compared with the result obtained by decrypting the signature block (data added by signature processing) by use of the public key corresponding to the private key which is used for the signature. If two results are equal each other, it is validated that the signature is correct and the signature target is not forged.

[0157] Herein, the public key corresponding to the private key used for the signature should be trusted for correct validation. The condition that it is included in the public lock list of the subject itself should be satisfied for validation. The signature is not validated unless the public key is trusted.

[0158] If the result of message digest is not equal to the result of decryption, then it is clear that the signature target has been forged.

[0159] The signature validation ~~flow~~ flowchart shown in FIG. 15 is described. In step 801, the signature target is subjected to message digest. The message digest means a ~~processing-process~~ for generating information consisting of 128 bits, which depends on the content of the target range independently of the data size of the target range as described ~~hereinbefore, above~~, because encryption of the entire target range of the signature requires a high cost. Next, in step 802, whether the public key corresponding to the private key used for signature is trustable or ~~not-not~~, is judged. If the public key is not trustable, then the signature validation is judged to be impossible in step 806.

[0160] If the public key is confirmed to be trustable in step 802, then the sequence proceeds to step 803, the signature block is decrypted by use of the public key corresponding

to the private key which is used for the signature, and the coincidence with the message digest is judged in step 804. This ~~processing process~~ is the actual signature validation step. If the coincidence is denied in step 804, then the signature is judged to be not correct, that is, the private key used for the signature is judged to be not correct in step 807. If the message digest is judged to be equal to the decryption result in step 804, then the signature is concluded to be correct in step 805.

[Group lock change]

[0161] A ~~flow~~-flowchart for group lock change is shown in FIG. 16. Four types of group lock change are described ~~herein under~~- below. In the flowchart, four types which are branched into four processing are described in the order from the left side.

A. Add now.

[0162] A new member is added. The added new member cannot decrypt the cryptography which has been encrypted before the addition. In this case, a pair of a new private key and public key is assigned to S_G and P_G of the group lock of the new version. The F value is "necessary". Therefore, the individual who receives the new version will not delete the previous version. The reason is that it is necessary for previous members to decrypt the cryptography encrypted before the addition.

B. Add retroactively.

[0163] A new member is added. The new member can also decrypt the cryptography encrypted before the addition. In this case, the previous S_G and P_G are used as they are. Therefore, F value is "unnecessary". The individual who receives the new version deletes the previous version. The new version may be used to decrypt the cryptography encrypted before the addition.

C. Delete now.

[0164] An existing member is deleted. The deleted member can decrypt the cryptography encrypted before the deletion. Of course, the deleted member cannot decrypt the cryptography encrypted after the deletion. In this case, a pair of private key and the public key is assigned to S_G and P_G of the group lock of the new version. Further F value is "unnecessary". As the result, the individual who receives the new version does not delete the previous version. The reason is that it is necessary for previous members including the deleted member to decrypt the cryptography encrypted before the deletion.

D. Delete retroactively.

[0165] An existing member is deleted retroactively. The deleted member cannot also decrypt the cryptography encrypted before the deletion. In this case, a pair of a new private key and public key is assigned to S_G and P_G of the group lock of the new version. Further, F value is "delete". As the result, the individual who receives the new version does not delete the previous version. The reason is that it is necessary for previous ~~members~~ members, excluding the deleted ~~member-member~~, to decrypt the cryptography encrypted before the deletion. However, in the case that the individual who ~~receives-receives~~, cannot acquire the private key of the new version, that is, the individual is the deleted member, the previous version is deleted. The reason is that the previous version is deleted so that the deleted member cannot also decrypt the cryptography encrypted before the deletion. The deletion of the group lock of the previous version by the deleted member is not guaranteed mathematically, but the deletion is promoted as a system in character.

[0166] When the group lock is changed, not only F value becomes meaningful but also the changing private key of the previous version is used for signature. The reason is that the new version is rendered trustable automatically in the case that the previous version is trusted as described hereinbefore. When the group lock is changed, the new group lock should be distributed promptly to ~~every-one~~ everyone who requires it.

[0167] The group lock changing ~~flow~~ flowchart shown in FIG. 16 and FIG. 17 is described in detail. In steps 901 and 902, a group lock to be changed is assigned, and the type of change is discriminated. In step 902, any one of addition processing and deletion processing is selected, in the case that addition and deletion are both involved as in the case of exchanging of the member, the order is set for each member and processing is executed for members one by one.

[0168] In the case that the change involves addition of a member in step 902, the sequence proceeds to step 903, the public key of the group or individual corresponding to the member to be added is selected from the public lock list. Next, in step 904, whether the addition is the addition now or the addition retroactively is judged. In other words, whether decryption of the cryptographic information encrypted in the past is set so as to be possible or ~~not-not~~, is determined. If the judgement in step 904 is NO, namely the addition from now, a group public key P_G , group private key S_G , and common key C_G are generated in step 905, and "F" which indicates how to deal with the group lock of the immediately precedent version is set ~~necessary~~ "necessary" in step 906. This indicates that the group lock of the new version and the group lock of the previous version ~~are~~ coexist. On the other hand, if the judgement in

step 904 is "add retroactively", the sequence proceeds to steps 907 and 908, S_G , P_G , and C_G of the group lock which is under ~~changing-changing~~, are set as S_G , P_G , and C_G of the changed group lock as they are, and F is set "unnecessary". This indicates that the group lock of the previous version is replaced completely with the group lock of the new version. Next, in step 909, the group private key S_G is encrypted by use of the common key C_U to generate $C_G(S_G)$, further C_G is encrypted by use of the public key P_{Mi} of the member including the added member to form an arrangement of $P_{Mi}(C_G)$ having the label LM corresponding to P_{Mi} as an index.

[0169] Next, a new changing right holder is set in step 910, a pair of a private key and a public key of the changing key is generated in step 911, and the private key of the changing key is encrypted by use of the public key of the new changing right holder in step 912.

[0170] Further, the version number V is updated in step 913, respective data are unified in step 914, a signature is executed by use of the changing private key for the unified data in step 915 to generate the signature result $Sig(S_U)$, and the data is further unified including the signature result in step 916. A signature is executed by use of the changing private key S_U' of the version before changing to generate $Sig(S_U')$ in step 917, and the changed group lock is added to the trust lock list of the generator in step 918, thus the changing procedure of the group lock is brought to an end.

[0171] If the change involves the deletion of a member in step 902, the sequence proceeds to step 919, and a member to be deleted is selected. Next, in step 920, whether the deletion involves "from now" or "retroactively" is judged. In other words, whether the condition is set so that the cryptographic information encrypted in the past can be decrypted or ~~not-not~~, is determined. If the judgement in step 920 is "NO", namely deletion from now, a group public key P_G , group private key S_G , and common key C_G are generated in step 921, and " F " for indicating how to deal with the group lock of the immediately precedent version is set ~~necessary-to~~ "necessary" in step 922. This indicates that the new group lock of the new version and the group lock of the previous version coexist. On the other hand, if the judgement in step 920 is "delete retroactively", then the sequence proceeds to steps 923 and 924, S_G , P_G , and C_G of the group lock which are now under changing are set as S_G , P_G , and C_G of the changed group lock as they are, and F is set "delete". Next, in step 925, the common key C_G is encrypted by use of the group private key S_G , further the common key C_G is encrypted by use of the public key P_{Mi} of the member who deletes the deleted member, and an

arrangement of P_{Mi} (C_G) having the label L_{Mi} corresponding to P_{Mi} as an index is formed. The procedure in step 910 and following steps is the same processing as performed in the case of addition.

[Application example]

[0172] FIG. 18 shows an application example to which the cryptography system described in the example is applied. In FIG. 18, a plurality of clients 20, a file server 30, and a directory server 40 are connected to a network 10. The network 10 may be LAN or WAN. The file server 30 stores files such as ~~documents~~—documents. The directory server 40 stores the group key. In this structure, for example, it is assumed that the client 20a stores a document in the file server 30. The client 20a extracts a desired group lock from the directory server 40, encrypts the document by use of the public key included in the extracted group lock, and stores the encrypted document 50a in the file server 30. When the client 20b wants to use the document, the client 20b extracts the document 50a from the file server 30 and extracts a desired group lock from the directory server 40 to acquire a private key, and decrypts the above-mentioned document by use of this private key.

[0173] In this structure, in the case that the client 20a writes a signature on the document and stores the document 50b with a signature in the file server 30, the client 20a extracts a desired group lock from the directory server 40 to acquire a private key of the group lock, and writes a signature by use of the private key. The client 20b can verify the signature of the document by use of the public key of the group lock.

[0174] In FIG. 18, the document of the file server 30 is the target to be processed by use of a group lock, but in the case that a mail server is used instead of the file server 30, the same encryption and decryption processing, and signature and verification processing are performed.

[0175] In the example of the present invention described hereinbefore, for example, the generation or change of decrypting ~~lock~~—lock, may be executed in an encrypting apparatus, a decrypting apparatus, or other apparatus in the third station, and that is true for other structural elements used in this public key cryptography system such as various lock lists.

[0176] In the present example, the target to be encrypted by use of a private key of a group/member is a common key consisting of a small number of bits (for example, 48 to 120 bits) and an amount of encryption processing is small, therefore a group lock is generated promptly at a reduced cost even though the number of members is large. ~~Further~~—Further, the

private key of the group lock appears only once in the cryptogram encrypted by use of the common key, therefore this system is preferable for maintaining the confidentiality.

[0177] In the present example, the private key of the group lock is encrypted by use of the common key, therefore a cryptogram is decrypted at a low cost in comparison with the case of encryption by use of the public key. The private keys S_G and S_U are not directly encrypted by use of the common keys C_G and C_U but modified private keys (S'_G , S'_U) may be encrypted by use of C_G and C_U . The relation between the modified private key and the original private key is specified as described herein under.

[Expression 4]

$$S'_G = f_G(S_G)$$

$$S'_U = f_U(S_U)$$

wherein functions F_G and F_U are not one directional function. Therefore, the functions F_G and F_U include inverse functions f_G^{-1} and f_U^{-1} represented by the following equations.

[Expression 5]

$$S_G = f_G^{-1}(S'_G)$$

$$S_U = f_U^{-1}(S'_U)$$

wherein modified functions f_G and f_U may be arbitrary functions as long as the inverse function exists and may be selected depending on the degree of required confidentiality.

[0178] The system structured as described herein above prevents an attacker from acquiring the private keys S_G and S_U even if the attacker decrypts the cryptograms $C_G(S'_G)$ and $C_U(S'_U)$ to acquire S'_G and S'_U because the attacker does not know the inverse function f_G^{-1} and f_U^{-1} .

[0179] Instead of the process in which the common keys C_G and C_U are encrypted by use of the public key of the group/member to generate cryptograms $P_{Mi}(C_G)$ and $P_{Mi}(C_U)$, the process in which a plain document is added with a so-called seed to encrypt the document may be used. This is represented as described herein under.

[Expression 6]

$$P_{Mi}(C_G + f_p(P_{Mi}))$$

$$P_{Mi}(C_U + f_p(P_{Mi}))$$

wherein f_p is a function which generates some output when the public key used for encryption is entered, for example, a hash function such as MD 5 or SHA 1 (brand name) may be used. The public key is different for every member, therefore the encryption target is different for every member, as the result the safety is improved.

[0180] In the above-mentioned example, because the common key is encrypted by use of the public key of each member, a plurality of cryptograms of C_G appears in the group lock. Even in this case, no hint is given to an attacker because of the seed.

[0181] In the above-mentioned example, the private key is encrypted by use of the common key and the common key is encrypted by use of the public key of the ~~member,~~ ~~however otherwise,~~ member. However, an encryption scheme in which the private key is directly encrypted by use of the public key of the member may be used. In such scheme, the above-mentioned seed may be used. In detail, the group key is structured so that the private keys S_G and S_U are included in $P_{Mi}(S_G)$ and $P_{Mi}(S_U)$ encrypted by use of the public key P_{Mi} of the member (common keys C_G and C_U are not used). In this case, $P_{Mi}(S_G + f_p(P_{Mi}))$ and $P_{Mi}(S_U + f_p(P_{Mi}))$ with seed is included in the group lock instead of $P_{Mi}(S_G)$ and $P_{Mi}(S_U)$.

[0182] As described ~~hereinbefore,~~ above, in the group type public key cryptography system of the present invention, the concept of group is introduced into the conventional public key cryptography system in which an individual is involved as a unit, the encryption processing of a plain document and the decryption processing of a cryptographic information by an arbitrary member who belongs to the ~~group-group,~~ can be executed by using the group public key and group private key which are generated with involving a group as a unit, and the combination of the individual public key and individual private key. According to the structure, it is possible for members of the group to hold cryptographic information in common based on the membership between the members in the group while the strict confidentiality is maintained between the inside of the group and the outside of the group. The proper encryption processing and validation of the proper encryption by the member in the group are possible by use of the electronic signature by the member who belongs to the group.

[0183] Further, in the group type public key cryptography system of the present invention, when a group lock is changed correspondingly to the change of a member who is a component of the group, a new pair of group public key and group private key is generated and registered at the time point when a member is changed, and the group lock can be changed easily correspondingly to the member change in structure. A signature written when the group lock is changed covers the entire arrangement of elements which constitute the group lock to thereby ensure the guarantee of the change.

[0184] Because the common key consisting of relatively small amount of data is encrypted by use of a cryptographic key to generate a group lock, the load for generating a

group lock is small. The private key itself of the group lock which is encrypted by use of the common key appears only once in the group lock, no hint is given to an attacker.